



Section 1: IDENTIFICATION

Product Name: Ag-Surf II

Pest Control Product Number: 30071

Product Use: Adjuvant.

Restrictions on Use: Not available.

Manufacturer/Supplier: Interprovincial Cooperative LTD. (IPCO)

945 Marion Street Winnipeg, MB R2J 0K7

Phone Number: 204.233.3461

Emergency Phone: CANUTEC: 1-888-CAN-UTEC (226-8832), 613-996-6666 or

*666 on a cellular phone.

Effective Date: February 27, 2025

Section 2: HAZARD(S) IDENTIFICATION

GHS INFORMATION

Classification: Flammable Liquids, Category 3

Acute Toxicity - Oral, Category 4 Skin Irritation, Category 2 Eye Damage, Category 1

LABEL ELEMENTS

Hazard

Pictogram(s):





Signal Word: Danger

Hazard Flammable liquid and vapor.

Statements: Harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical, ventilating, and lighting equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves, protective clothing and eye protection.





Response: IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Rinse mouth.

If skin irritation occurs: Get medical attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use dry chemical, CO2, water spray or alcohol-resistant foam to

extinguish.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents and container in accordance with applicable regional,

national and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: None.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200).

This material is considered hazardous by the Hazardous Products Regulations.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS							
Hazardous Ingredient(s)	Common name / Synonyms	CAS No.	% wt./wt.				
Alcohols, C9-11, ethoxylated 1-Propanol, 2-methyl-	Not available. Isobutyl alcohol	68439-46-3 78-83-1	89.24 - 94.76 5.24 - 10.76				

Section 4: FIRST-AID MEASURES

Inhalation: If inhaled: Call a poison center or doctor if you feel unwell.

Acute and delayed symptoms and effects: May cause respiratory irritation.

Signs/symptoms may include cough, sneezing, nasal discharge,

headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness. Inhalation of high concentrations of Isobutyl alcohol can cause central nervous system damage, pulmonary edema, and liver

damage. Death may occur from respiratory failure.

Eye Contact: If in eyes: Rinse cautiously with water for at least 30 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Immediately

call a poison center or doctor.

Acute and delayed symptoms and effects: Causes serious eye damage. Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or

complete loss of vision.





Skin Contact: If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water or shower. If skin irritation occurs: Get medical attention.

Wash contaminated clothing before reuse.

Acute and delayed symptoms and effects: Causes skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Ingestion: If swallowed: Rinse mouth. Call a poison center or doctor if you feel

unwell. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious

person.

Acute and delayed symptoms and effects: Harmful if swallowed. May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. Ingestion of large doses of Isobutyl alcohol may cause central nervous system damage, pulmonary edema, and liver damage. Death may occur from respiratory failure.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately

(show the label or SDS where possible).

Note to Physicians: Symptoms may not appear immediately. In case of ingestion of

Ethoxylated alcohols, if victim is a child, give no more than 1 glass of water and 15 cc (1 Tablespoon) syrup of IPECAC. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before emesis, gastric lavage should be considered following intubation with a cuffed

endotracheal tube.

Section 5: FIRE-FIGHTING MEASURES

FLAMMABILITY AND EXPLOSION INFORMATION

Flammable liquid and vapor. Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Liquid is lighter than water.

If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

Fire involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

Sensitivity to Mechanical Impact: This material is not sensitive to mechanical impact.

Sensitivity to Static Discharge: Take action to prevent static discharges. This material is

sensitive to static discharge.

MEANS OF EXTINCTION





Suitable Extinguishing Media: Small Fire: Dry chemical, CO2, water spray or alcohol-

resistant foam.

Large Fire: Water spray, fog or alcohol-resistant foam. Move

containers from fire area if you can do it without risk.

Unsuitable Extinguishing Media: Do not use straight stream.

Products of Combustion: Oxides of carbon.

Protection of Firefighters: Inhalation or contact with material may irritate or burn skin

and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited

protection.

Section 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures: As an immediate precautionary measure, isolate spill or leak area

for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. ELIMINATE all invition courses (no amplion, flores, appelies, or flores) in

ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product

must be grounded.

Personal Precautions: Do not touch or walk through spilled material. Use personal

protection recommended in Section 8.

Environmental Precautions: Prevent entry into waterways, sewers, basements or confined

areas.

Methods for Containment: Stop leak if you can do it without risk. A vapor suppressing foam

may be used to reduce vapors.

Methods for Clean-Up: Absorb or cover with dry earth, sand or other non-combustible

material and transfer to containers. Use clean non-sparking tools

to collect absorbed material.

Other Information: See Section 13 for disposal considerations.

Section 7: HANDLING AND STORAGE

Handling:

Do not swallow. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. See Section 8 for information on Personal Protective Equipment.

Storage:

Store in a well-ventilated place. Keep cool. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION





Exposure Guidelines Component

Alcohols, C9-11, ethoxylated [CAS No. 68439-46-3]

ACGIH: No TLV established.
OSHA: No PEL established.
Isobutyl alcohol [CAS No. 78-83-1]

ACGIH: 50 ppm (TWA); (1973)

OSHA: 100 ppm (TWA), 300 mg/m³ (TWA);

50 ppm (TWA) [Vacated];

PEL: Permissible Exposure Limit TLV: Threshold Limit Value TWA: Time-Weighted Average

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels

of dust, fume, vapour, gas, etc.) below recommended exposure limits. Use explosion-proof electrical, ventilating,

and lighting equipment.

PERSONAL PROTECTIVE EQUIPMENT (PPE)











Eye/Face Protection: Wear chemical safety goggles. Ensure that eyewash

stations and safety showers are close to the workstation location. Use equipment for eye protection that meets the standards referenced by CSA Standard CAN/CSA-Z94.3-92 and OSHA regulations in 29 CFR 1910.133 for Personal

Protective Equipment.

Hand Protection: Wear protective gloves. Consult manufacturer specifications

for further information.

Skin and Body Protection: Wear protective clothing. Flame resistant clothing that meets

the NFPA 2112 and CAN/CGSB 155.20 standards is

recommended in areas where material is stored or handled.

Respiratory Protection: If engineering controls and ventilation are not sufficient to

control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4-11, with organic vapor cartridge, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-

purifying respirators.

General Hygiene Considerations: Handle according to established industrial hygiene and

safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to



ensure adequate protection.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Hazy liquid. Colour: Colourless.

Odour: Slight.

Odour Threshold: Not available.

Physical State: Liquid. pH (1% wt/wt): 6.7

Melting Point / Freezing

Point:

3 °C (37.4 °F)

Initial Boiling Point: 100 °C (212 °F)

Boiling Range: Not available.

Flash Point: > 46.7 °C (116.06 °F) (TCC)

Evaporation Rate: Not available. Flammability (solid, gas):

Not applicable.

Lower Flammability Limit: 0.096 % (estimated) **Upper Flammability Limit:** 0.872 % (estimated)

Vapor Pressure: Not available. Vapor Density: Not available.

0.9706 (Water = 1) at 20 °C (68 °F) **Relative Density:**

Solubilities: Miscible in water.

Partition Coefficient: n-

Octanol/Water:

Not available.

Auto-ignition Temperature: Not available. **Decomposition** Not available.

Temperature:

Not available. **Viscosity:** Percent Volatile, wt. %: Not available. VOC content, wt. %: Not available. Density: Not available.

Coefficient of Water/Oil

Distribution:

Not available.

Section 10: STABILITY AND REACTIVITY





Reactivity: Contact with incompatible materials. Sources of ignition. Exposure to

heat.

Chemical Stability: Stable under normal storage conditions.

Possibility of Hazardous

Reactions:

None known.

Conditions to Avoid: Contact with incompatible materials. Sources of ignition. Exposure to

heat.

Incompatible Materials: Strong acids. Strong oxidizers. Strong reducers.

Hazardous Decomposition Products: Not available.

Section 11: TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE

Product Toxicity

Oral: 2000 mg/kg (rat), estimated

Dermal: > 5000 mg/kg (rat), estimated

Inhalation: Not available.

Component Toxicity

Component CAS No. LD50 oral LD50 dermal LC50

Alcohols, C9-11, 68439-46-3 1378 mg/kg (rat) > 2000 mg/kg Not available.

ethoxylated (rabbit)

Isobutyl alcohol 78-83-1 2460 mg/kg (rat) 3400 mg/kg (rabbit) 8000 ppm (rat); 4H

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion. Skin absorption.

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Lungs.

Liver. Central nervous system.

Symptoms (including delayed and immediate effects)

Inhalation: May cause respiratory irritation. Signs/symptoms may include cough, sneezing,

nasal discharge, headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness. Inhalation of high concentrations of Isobutyl alcohol can cause central nervous system damage, pulmonary edema, and liver damage. Death may

occur from respiratory failure.

Eye: Causes serious eye damage. Signs/symptoms may include cloudy appearance of

the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired

vision or complete loss of vision.

Skin: Causes skin irritation. Signs/symptoms may include localized redness, swelling,

and itching.

Ingestion: Harmful if swallowed. May cause gastrointestinal irritation. Signs/symptoms may

include abdominal pain, stomach upset, nausea, vomiting and diarrhea. Ingestion of large doses of Isobutyl alcohol may cause central nervous system damage, pulmonary edema, and liver damage. Death may occur from respiratory failure.

Skin Sensitization: Not available.





Respiratory Sensitization: Not available.

Medical Conditions Not available.

Aggravated By Exposure:

EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Lungs. Liver.

Central nervous system.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Carcinogenicity: This product does not contain any carcinogens or potential

carcinogens above reportable thresholds as listed by ACGIH, IARC,

OSHA, or NTP.

Mutagenicity: Not available.

Reproductive Effects: Not available.

Developmental Effects

Teratogenicity: Not available.

Embryotoxicity: Not available.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Not available.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Other Adverse Effects: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions: Disposal should be in accordance with applicable regional, national

and local laws and regulations. Local regulations may be more

stringent than regional or national requirements.

Section 14: TRANSPORT INFORMATION



Product in small means of containment (<450 L) is exempt from the requirements of the Canadian Transport of Dangerous Goods Regulations and those of the US Hazardous Materials Regulations.

If transported in large means of containment (> 450L):

U.S. Department of Transportation (DOT)

Proper Shipping Name: UN1987, ALCOHOLS, N.O.S. (Isopropanol), 3, PG III

Class: 3

UN Number: UN1987

Packing Group: |||

Label Code:

FLAMMABLE 3

Canada Transportation of Dangerous Goods (TDG)

Proper Shipping Name: UN1987, ALCOHOLS, N.O.S. (Isopropanol), 3, PG III

Class: 3

UN Number: UN1987

Packing Group: |||

Label Code:



Section 15: REGULATORY INFORMATION

Chemical Inventories

US (TSCA)

The components of this product are in compliance with the chemical notification requirements of TSCA.

Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.

Federal Regulations

United States

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA Title III

Component	Section 302 (EHS) TPQ	Section 304 EHS RQ	CERCLA RQ (lbs.)	Section 313	RCRA CODE	CAA 112(r) TQ
	(lbs.)	(lbs.)				(lbs.)
Isobutyl alcohol	Not listed.	Not listed.	5000	Not listed.	U140	Not listed.

State Regulations Massachusetts

US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of



Ag-Surf II

Massachusetts Regulations Section 670.000)

ComponentCAS No.RTK ListIsobutyl alcohol78-83-1Listed.

Note: E = Extraordinarily Hazardous Substance

New Jersey

US New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated

Section 34:5A-5)

SAFETY DATA SHEET

ComponentCAS No.RTK ListIsobutyl alcohol78-83-1SHHS

Note: SHHS = Special Health Hazard Substance

Pennsylvania

US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Component
CAS No.
RTK List
Isobutvl alcohol
78-83-1
E

Note: E = Environmental Hazard

California

California Prop 65: This product does not contain chemicals known to the State of California

to cause cancer, birth defects or other reproductive harm.

Canada

Pest Control Products Act (PCPA) Registration Number: 30071

Read the PCPA label, authorized under the Pest Control Products Act, prior to using or handling this pest control product.

This chemical is a pest control product registered by Health Canada Pest Management Regulatory Agency and is subject to certain labelling requirements under the Pest Control Products Act (PCPA). There are Canada-specific environmental requirements for handling, use, and disposal of this pest control product that are indicated on the label. These requirements differ from the classification criteria and hazard information required for GHS-consistent safety data sheets. Following is the hazard information required on the pest control products label: Read the label and booklet before using. Keep out of reach of children.

Section 16: OTHER INFORMATION

Revision Date/Reason: February 27, 2025/ Section 15 updated

Notice: The enclosed information is supplied as customer service and is

provided in good faith. Although it has been based on data drawn from sources deemed to be reliable, Interprovincial Cooperative

Limited cannot guarantee its accuracy and assumes no

responsibility for conditions resulting from its use.